

Product Specifications

EXPS15LCD

PRODUCT FEATURES

- * 15" LCD Monitor
- * High Quality Display
- * Composite Video Signal Input
- * Plain Board Design
- * Adjustable angles
- * IP65
- * Indoor and Outdoor installation
- * NTSC & PAL
- * VGA Port
- * Standard Video Port



DESCRIPTION

The EXPS15LCD is a high-end explosion proof monitor that will fit applications with the most extreme conditions without jeopardizing quality image.

The EXPC15LCD Monitors present bright images, intense colors, and enhanced details in clear highdefinition. Designed and tested for commercial video security use, the slim design of these EXPS15LCD monitors take up minimal space thanks to the design and has an easy installation process.

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---|
| Imaging Device | 15" LCD Monitor |
| Color | 16770000 |
| Pixel Distance | 0.297mm |
| View Area | 304.1mm (W) x 228.1mm (H) |
| Contrast | 500:1 |
| Brightness | 300cd/m2 |
| Horizontal Angle | 140° (CR>5) |
| Pitching Angle | 140° (CR>5) |
| Response Time | 16ms |
| Horizontal Refresh | 38 ~ 60Khz |
| Pitching Refresh | 56 ~ 75Khz |
| Bandwidth | 80MHz |
| Resolution | 1024 x 768 |
| Power Requirements | 100VAC~240VAC~50/60Hz |
| Power Consumption | 24W |
| Current | <300mA |
| Signal | 1 Vp-p Composite video |
| Resistance | 75Ohms |
| Joint | Video cable and power cable out |
| RGB Input | 15-pin D-SUB |
| S-VHS Input | 4-pin Mini DIN |
| Panel | 1 for On/Off Power |
| Connections | 2-core power cable / 1-core video cable |
| Weight | 28Kg |
| Ship Weight | 31Kg |
| Dimension | 460(L) x 336(H) x 220(W)mm |
| Window Thickness | 12mm |
| Window Area | 306 x 230mm |
| Cable outlets | 2 |
| Screw Type | G-34" |
| Mounting | Stand or by suspending Bracket <60W |
| Operating Temperature | 0°C to ~+ 50°C |
| Air Pressure | 86 ~ 106Hpa |
| Humidity | < 95% RH (+25° C) |
| CERTIFICATIONS | IP65 |